



Quantum® Die-Cast Competitive Comparison

	Lithonia Quantum®	TCP®	Mule®	EELP®	Exitronix®	Symkar®
Family / Model	LQC	26 Series	MD	CA	400	SDC
Dimensions	11.75" W 8.25" H 2.0" D	12.75" W 9.0" H 2.0" D	12.75" W 8.5" H 2.0" D	12.75" W 9.0" H 2.0" D	12.75" W 8.5" H 2.0" D	13.0" W 8.5" H 1.75" D
Standard Finishes	Black with Brushed Aluminum, Faceplate	Black with Brushed Aluminum, Faceplate	No Standard, Must Designate, Finish	No Standard, Must Designate, Finish	No Standard, Must Designate, Finish	No Standard, Must Designate, Finish
Temp Rating / Damp Location	Damp Listed Standard	Damp Listed Standard	Damp Listed as an Option	Damp Listed Standard	Damp Listed Standard	Damp Listed Standard
Power Rating	120/277 VAC 1.2 W (max)	120/277 VAC 4.0 W (max)	120/277 VAC 4.0 W (max)	120/277 VAC 4.0 W (max)	120/277 VAC 2.0 W (max)	120/277 VAC 3.0 W (max)
Operation	AC and Emergency	AC and Emergency	AC and Emergency	AC and Emergency	AC and Emergency	AC and Emergency
Warranty	5 Year Full	5 Year, Pro-rated Battery	5 Year Limited	5 Year	5 Year, 5 Year Pro-rated Battery	5 Year, 5 Year Pro-rated Battery
Listing	UL	UL	ETL	UL and ET	UL	UL and ETL
Features / Accessories	Knockouts, 1 or 2 Face, Face Plate Kit	Universal Knockouts, 1 or 2 Face	Universal Knockouts, 1 or 2 Face	Universal Knockouts, 1 or 2 Face	Universal Knockouts, 1 or 2 Face	Universal Knockouts, 1 or 2 Face
Mounting Configuration	Patented Quick-Mount Universal (Top, end or back) Mounting	Traditional Hardware for Universal (Top, end or back) Mounting	Traditional Hardware for Universal (Top, end or back) Mounting	Traditional Hardware for Universal (Top, end or back) Mounting	Traditional Hardware for Universal (Top, end or back) Mounting	Traditional Hardware for Universal (Top, end or back) Mounting